



Specifications:

Model No. (X=1: →Clockwise) (X=2: ←Anticlockwise)	Freq. Range MHz	IL. dB (max)	Isolation dB (min)	VSWR	Forward Power CW	Reverse Power W
SMTG-D35.0- X /300-320MHz	300-320	0.60	20.0	1.25	150	20/100
SMTG-D35.0- X /300-350MHz	300-350	0.80	18.0	1.35	150	20/100
SMTG-D35.0- X /310-340MHz	310-340	0.50	20.0	1.25	150	20/100
SMTG-D35.0- X /320-340MHz	320-340	0.45	20.0	1.25	150	20/100
SMTG-D35.0- X /350-370MHz	350-370	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /350-400MHz	350-400	0.50	19.0	1.25	150	20/100
SMTG-D35.0- X /361-366MHz	361-366	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /370-420MHz	370-420	0.50	19.0	1.25	150	20/100
SMTG-D35.0- X /380-410MHz	380-410	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /380-460MHz	380-460	0.50	18.0	1.30	150	20/100
SMTG-D35.0- X /390-410MHz	390-410	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /400-420MHz	400-420	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /400-440MHz	400-440	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /400-450MHz	400-450	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /400-470MHz	400-470	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /400-500MHz	400-500	0.50	19.0	1.25	150	20/100
SMTG-D35.0- X /410-460MHz	410-460	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /420-430MHz	420-430	0.30	25.0	1.15	150	20/100
SMTG-D35.0- X /420-450MHz	420-450	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /420-480MHz	420-480	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /430-440MHz	430-440	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /430-470MHz	430-470	0.40	20.0	1.25	150	20/100
SMTG-D35.0- X /440-470MHz	440-470	0.30	23.0	1.20	150	20/100
SMTG-D35.0- X /450-456MHz	450-456	0.25	25.0	1.15	150	20/100
SMTG-D35.0- X /450-500MHz	450-500	0.40	20.0	1.25	150	20/100



Model No. (X=1: →Clockwise) (X=2: ←Anticlockwise)	Freq. Range MHz	IL. dB (max)	Isolation dB (min)	VSWR	Forward Power CW	Reverse Power W
SMTG-D35.0-X/450-520MHz	450-520	0.40	20.0	1.25	150	20/100
SMTG-D35.0-X/450-550MHz	450-550	0.40	20.0	1.25	150	20/100
SMTG-D35.0-X/455-465MHz	455-465	0.25	25.0	1.15	150	20/100
SMTG-D35.0-X/459-486MHz	459-486	0.30	23.0	1.20	150	20/100
SMTG-D35.0-X/470-490MHz	470-490	0.30	23.0	1.20	150	20/100
SMTG-D35.0-X/470-530MHz	470-530	0.40	20.0	1.20	150	20/100
SMTG-D35.0-X/470-570MHz	470-570	0.40	20.0	1.25	150	20/100
SMTG-D35.0-X/470-610MHz	470-610	0.50	18.0	1.30	150	20/100
SMTG-D35.0-X/475-525MHz	475-525	0.30	23.0	1.20	150	20/100
SMTG-D35.0-X/495-516MHz	495-516	0.30	23.0	1.20	150	20/100
SMTG-D35.0-X/500-600MHz	500-600	0.40	20.0	1.20	150	20/100

Instructions:

- 1, When the surface attachment isolator adopts reflow welding process, the maximum temperature does not exceed 260 degrees;
- 2, The reflected power is only 10W, if you need more can use the way of circulator plus resistance;
- 3, Only some common frequencies in the table, can be produced according to the user's requirements;
- 4, If you do not find what you are looking for, please contact us!