


3.0 to 6.0GHz Drop in Isolator

WG2528C Drop-In Type

Outline Drawing (mm):



Features:

- ✧ Good temperature stability
- ✧ Withstand high power
- ✧ RoHS compliant
- ✧ Weight : ≈ 55 g


Material list:

- ✧ Housing: Aluminum
- ✧ Coating: Nickel
- ✧ Inner conductor: brass
- ✧ Plating layer: silver

Application:


- ✧ Rf amplifier final stage, protect the amplifier
- ✧ Common transceiver antenna
- ✧ Used in civil, military, aerospace and other fields

Order Examples :



Basic Specifications :

Impedance	50 Ω
Size(mm)	25.4*28.0*14.0
Operating Temp	-10~+60℃
Storage temperature	-50~+90 ℃



Specifications:

Model No. (X=1: →Clockwise) (X=2: ←Anticlockwise)	Freq. Range GHz	IL.dB (max)	Isolation dB (min)	VSWR	Forward Power CW	Reverse Power W
WG2528C-X-100/3.0-4.0GHz	3.0-4.0	0.50	18.0	1.25	100	100
WG2528C-X-100/3.0-5.0GHz	3.0-5.0	0.50	18.0	1.25	100	100
WG2528C-X-100/3.0-6.0GHz	3.0-6.0	0.50	18.0	1.30	100	100
WG2528C-X-100/4.0-5.0GHz	4.0-5.0	0.40	20.0	1.25	100	100
WG2528C-X-100/4.0-6.0GHz	4.0-6.0	0.45	20.0	1.25	100	100
WG2528C-X-100/5.0-6.0GHz	5.0-6.0	0.40	20.0	1.25	100	100

If the frequency range you need is not covered in the form.
Please contact us for details.